

95 Applications™ SLICK BARRIERSM

SLICK BARRIERSM

Propriety trade secret protected. Creates a tile like glaze smooth coating on vertical surfaces strategically applied around structures and items. Used as a physical barrier on vertical surfaces in order discourage access. Only to be used with the written consent of 95 Applications™ LLC.

SLICK BARRIERSM is a branded product and Proprietary Intellectual Property owned by 95 Applications™.

APPLICATION INSTRUCTIONS:

Not for resale and commercial use ONLY. Please refer to 95 Applications™ Certified Technician and/or the 95 Applications™ Operation Manual for additional instructions.

CLEAN UP:

Handle in accordance with good industrial hygiene and safety practice. Use dry sand to contain the flow of material.

COVERAGE RATES:

One gallon will cover approximately 100 to 300 square feet depending on the finish and porosity of the surface to be treated.

KEEP OUT OF REACH OF CHILDREN

NOT FOR RESALE



Made in USA

SLICK BARRIER

<input type="checkbox"/> 1 US GALLON	CLEAR
<input type="checkbox"/> 5 US GALLON	DURABLE
<input type="checkbox"/> 55 US GALLON	QUICK DRYING TIME

U.S. Pat. App. Ser. No. 16/709,371
U.S. Pat. App. Ser. No. 17/010,803
U.S. Prov. Pat. Ser. No. 63/119,589

DANGER:

This product may contain a chemical known to the state of California to cause cancer. May damage fertility. May cause damage to organs through prolonged or repeated exposure.

PRECAUTIONARY STATEMENTS:

GENERAL: KEEP OUT OF THE REACH OF CHILDREN. PREVENTION: Do not handle it until all safety precautions have been read and understood. Ensure adequate ventilation, especially in confined areas. Obtain special instructions before use. **CLEAN UP** - Prevent further leakage or spillage if safe to do so. Dike far ahead of spill; use dry sand to contain the flow of material. Handle in accordance with good industrial hygiene and safety practice. Keep the container tightly closed. This product, as supplied, does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies. **RESPONSE:** If on skin (or hair): Rinse skin with water/shower. Eye contact, rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. If exposed or concerned: Get medical advice/attention if you feel unwell. **DISPOSAL:** Disposal should be in accordance with applicable regional, national and local laws and regulations. Do not reuse container. This Product contains substances which are regulated pollutants pursuant to the Clean Water Act (please see SDS). Transport - Not Regulated. This product is not considered hazardous by the 2012 OSHA Hazard Communication Standard.

CONTACT YOUR LOCAL POISON CONTROL CENTER OR CALL 1-800-457-4280 (North America). INFOTRAC 01-352-323-3500 (International).

Specifications/Characteristics
Water-base emulsion polymers
Appearance Milky Liquid
Physical State Liquid
Odor Slight
Contains Less Than 100 g/l
Meets ASTM 1315-95 & ASTM C-309-1
SB1977WBv1 **PATENT PENDING**

MANUFACTURED FOR: 95 Applications™, Gilbert, AZ 480-202-5500

